

LISTING OF CLAIMS:

1-12. (cancelled)

13. (currently amended) A communications receiver, comprising:

a chaotic oscillator having an oscillator portion and a chaotic portion with a non-linear resistance element such that when said oscillator and chaotic portions are coupled, they form a said chaotic oscillator;

a synchronizing resistor that couples said oscillator portion and said chaotic portion to pass a current signal therebetween;

said oscillator portion being signally coupled to a communications medium carrying a modulated chaotic signal;

said chaotic portion being signally coupled directly to said communications medium such that a voltage of said communications medium is directly applied to said chaotic portion through a circuit path parallel to a coupling allowing said current signal to pass between said oscillator portion and said chaotic portion;

a comparator having a first input coupled to said communications channel and a second input coupled to said chaotic portion, wherein the synchronizing resistor is adjusted so that an output of said comparator is clean and clear, and wherein the output of said comparator indicates, by nominal zero levels, a difference between a frequency characterizing said modulated chaotic signal and a frequency of said chaotic portion; and

said chaotic portion being coupled to said communications medium through a resistor bridging said first and second inputs of said comparator.

14. (canceled)

15. (previously presented) A device as in claim 13, wherein said chaotic portion includes a capacitor coupled to said non-linear resistance element.

16. (currently amended) A device as in claim ~~14~~ 13, wherein said oscillator portion includes a tank circuit.

17. (currently amended) A device as in claim ~~14~~ 13, further comprising a beat detector coupled to said comparator output.

18. (currently amended) A device as in claim ~~14~~ 13, further comprising a counting circuit connected to said comparator output.

19. (currently amended) A communications device, comprising:

a chaotic oscillator connectable to a communications channel;

said chaotic oscillator having a tank circuit with at least two capacitors and an inductor and having an effective capacitance determined by said at least two capacitors;

a first of said at least two capacitors being connected to ~~an~~said inductor and a second of said at least two capacitors being selectively connectable to said inductor to combine respective capacitances of said at least two capacitors through a switch, wherein said second of said at least two capacitors is isolated from said chaotic oscillator by said switch;

said switch having an input for accepting an information signal and being controllable responsibly to said information signal without transforming said information signal, wherein said effective capacitance does not include said second of said at least two capacitors when said switch is switched to a first state, wherein said effective capacitance includes said second of said at least two capacitors when said switch is switched to a second state, wherein said chaotic oscillator is selectively alternated between at least two oscillating regimes and thereby modulated in accord with said information signal to generate a chaotic signal which at each instant oscillates according to a selected one of said oscillating regimes, and wherein a first oscillating regime being associated with said first state of said switch and a second oscillating regime being associated with said second state of said switch;

a receiver signally coupled to said communications channel; and

said receiver having a receiving chaotic oscillator portion for each of said at least two oscillating regimes, each portion being configured to synchronize with a respective one of said at least two ~~chaotic signals~~ oscillating regimes.

20. (previously presented) A device as in claim 19, further comprising a detector connected to detect which of said at least two oscillating regimes is currently synchronized and to generate an output indicating the same such that said information signal is recovered from said chaotic signals.

21. (cancelled)

22. (previously presented) A chaotic communications system, comprising:

a transmitter;

a receiver;

said transmitter having first and second subsystems, said first subsystem being connected to apply a first signal generated in said first subsystem to said second subsystem;

said receiver having third and fourth subsystems, said third subsystem being connected to apply a third signal generated in said third subsystem to said fourth subsystem;

said second subsystem being connected to apply a second signal generated in said second subsystem to said first subsystem;

one of said first subsystem and said second subsystem being drivable by one of an external driving signal, an external current source, and a pre-established initial state where said first and second subsystems are lossless where said first and second subsystems are generated numerically by a computer;

said first and second subsystems being configured such that a chaotic oscillation is maintained therebetween, whereby said first and second signals are chaotic,

said transmitter further including a modulator responsive to an external information signal connected such that said chaotic oscillation is perturbed and a modulated signal derived thereby or a signal derived from said chaotic oscillation unperturbed is augmented such that said signal is modulated;

said transmitted second signal being connectable through a communication channel connectable to said third subsystem, whereby a received version of said second signal is applied to said third subsystem;

said receiver also having a synchronizing filter for applying a filtered version of said received second signal to said fourth subsystem;

said receiver having a decoder connected to derive a received information signal from said received second signal by comparing said received second signal, without transforming said received second signal, to a signal inhering in said receiver.